

恒天创丰 混凝土泵车

CITY CHUANG FENG HEAVY INDUSTRY Truck Mounted Concrete Pump

HT5310THB 42 | HT5330THB 46 | HT5330THB 48 | HT5430THB 52 | HT5440THB 55 | HT5530THB 60

- 5 节 Z 型臂架，末端臂展开角度大，展开、收拢快，操作灵活方便
- 5 sections Z form boom, the end arm angle is various, folding and unfolding very fast
- X 支腿，适合狭窄场地施工
- X legs, suitable for narrow jobsite
- 泵送排量 大，无级调节，满足各种工况需求
- The output of the delivery pump is very high, continuously adjust, suitable for all the jobs
- 节能控制系统，自动匹配功率
- Energy control system, match the power automatically
- 先进的润滑系统，臂架摆动小，寿命更长
- Advanced lubrication system, low boom vibration, long service life
- 臂架减震系统，末端振幅控制在 50 毫米内，改善操作性能
- Boom vibration control system, boom amplitude control within 50mm, improve operation performance



主要技术参数 Main Technical Parameters

型号 Model	HTS310THB 42	HTS330THB 46	HTS330THB 48	HTS430THB 52	HTS440THB 55	HTS530THB 50
最大排量 (m³/h) Maximum output	170	170	170	170	170	225
混凝土缸尺寸 (mm) Concrete cylinder	Φ230×2100	Φ230×2100	Φ230×2100	Φ230×2100	Φ230×2100	Φ280×2100
转向次数 Stroke per minute	32	32	32	32	32	29
混凝土压力 (MPa) Concrete pressure	7.2	7.2	8.75	8.75	8.75	8.75
料斗容积 (m³) Hopper capacity	0.6	0.6	0.6	0.6	0.6	0.6
分配阀形式 Distribution valve	S阀	S阀	S阀	S阀	S阀	S阀
最大骨料粒径 (mm) Max. aggregate size	40	40	40	40	40	40
垂直高度 (m) Vertical reach	41.4	45.3	47.3	51.3	54.3	59.3
水平长度 (m) Horizontal reach	37.4	41.3	43.3	47.5	50.2	55.3
最小展开高度 (m) Unfolding height	8.75	8.71	10.6	11.3	11.9	16.5
最大泵送深度 (m) The maximum pumping depth	29.1	33.1	34.3	38.4	40.2	44.6
各臂转角 (°) Section articulation	92/180/239/180/250	92/180/225/180/245	92/180/225/183/210	92/180/225/180/210	92/180/225/180/210	92/180/210/180/180/210
转台旋转角 (°) Rotation	370	370	370	370	370	370
输送管直径 (mm) Delivery line	126	126	125	125	125	125
前支腿间距 (m) Outfitter spread-front	7.82	8.90	8.87	9.1	9.1	12.1
后支腿间距 (m) Outfitter spread-rear	9.08	9.50	10.1	10.6	10.6	13.6
前支腿距车 (m) Front and rear legs distance	8.37	8.8	9.4	9.96	9.96	12.6
臂架形式 Arm form	Z	Z	Z	Z	Z	RZ
整车型号 Mode	HTS310THB	HTS330THB	HTS330THB	HTS430THB	HTS440THB	HTS530THB
底盘型号 Chassis Model	五十铃CY23Q 6×4	五十铃CY23Q 6×4	五十铃CY23Q 6×4	奔驰ACTROS41 8×4	奔驰ACTROS41 8×4	奔驰ACTROS41 8×4
发动机排放标准 Emission	国IV GBIV	国IV GBIV	国IV GBIV	国IV GBIV	国IV GBIV	国IV GBIV
外形尺寸 (长×宽×高) (mm) Overs: (Length×Width×Height)	11928×2500×4000	11860×2600×4000	13000×2600×4000	14050×2500×4000	14050×2500×4000	15430×2500×4000
总质量 (t) Total weight	31	33	33	43	44	53
额定功率 (kW) Rated Power	294	294	294	300	300	300



CHTC 恒天创丰

地址: 江苏大丰市大中镇工业园兴业路 66 号 邮编: 224300

☎ 0515-83532388 ☎ 0515-83688508 ✉ szcf_0111@126.com www.htjvcf.com